

ALPINE RST Super 15W-40

High-performance universal engine oil

Properties

Alpine RST Super is a mineral high-performance universal engine oil of viscosity class SAE 15W-40. Base oils produced with the latest refinery technology and carefully selected innovative additives guarantee that the product meets the highest requirements. Among its most outstanding properties are the excellent shear stability at high temperatures and exceptional wear protection under all operating conditions. Cleaning additives prevent deposits, keep pistons and valves clean and protect the engine against black sludge. Clean engines and low friction reduce energy loss in the engine and minimise servicing costs.

Use instructions

Alpine RST Super is a high-performance engine oil for universal use, even under heavy-duty conditions. It is recommended for passenger car petrol and diesel engines with or without turbocharging. It meets the stringent requirements of modern fuel-efficient engines and the latest emissions standards with a generous safety margin.

Performance data

Specifications: ACEA A3/B3/B4-04/E2 – 96 • API SJ/CF-4
Approvals: MB approval 229.1

TYPICAL VALUES	METHOD	UNIT	ALPINE RST Super
SAE class	DIN 51 511	-	15W-40
Density at 15°C	DIN 51 757	g/cm ³	0.881
Viscosity at -20°C	DIN 51 377	mPa s	6400
Viscosity at 40°C	DIN 51 562	mm ² /s	105
Viscosity at 100°C	DIN 51 562	mm ² /s	13.9
Viscosity index (VI)	DIN ISO 2909	-	133
COC flash point	DIN ISO 2592	°C	225
Pour point	DIN ISO 3016	°C	- 30
Total base number	DIN ISO 3771	mgKOH/g	10.4
Sulphated ash	DIN 51 575	g/100 g	1.3

The above values may vary within commercially accepted tolerances

June 2016